

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
12 July 2001 (12.07.2001)

PCT

(10) International Publication Number
WO 01/50020 A1

(51) International Patent Classification: F04B 19/22

[KR/KR]; Jukong Apt. 804-404, 270, Haan 3-Dong, Kwangmyung, Kyungki-do 423-063 (KR).

(21) International Application Number: PCT/KR99/00794

(22) International Filing Date:
21 December 1999 (21.12.1999)

(74) Agents: PARK, Jang, Won et al.; Park, Kim & Partner, Jewoo Building, 4th floor, 200, Nonhyun-Dong, Kangnam-ku, Seoul 135-010 (KR).

(25) Filing Language: Korean

(26) Publication Language: English

(81) Designated States (national): CN, DE, US.

(71) Applicant (for all designated States except US): LG ELECTRONICS INC. [KR/KR]; 20, Yoido-Dong, Yongdunpo-Ku, Seoul 150-010 (KR).


Published:
— With international search report.

(72) Inventor; and

(75) Inventor/Applicant (for US only): SONG, Gye, Young

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PISTON SUPPORTING STRUCTURE FOR LINEAR COMPRESSOR



(57) Abstract: The present invention relates to a piston supporting structure for the linear compressor in accordance with the present invention, including a piston reciprocating in the axial direction in receipt of driving force of a motor, a first spring of which one end portion is fixed to one side of the piston, and a second spring of which one end portion is fixed to the other side of the piston. In the present invention, the first and second springs elastically supporting the piston reciprocating in receipt of driving force of the motor are contracted and relaxed in the axial direction without being displaced in a radius direction, and thereby elastically support the reciprocating movement of the piston, so that the piston can linearly reciprocate in the axial direction in the compression space of the cylinder. Accordingly, a rotation moment is not applied to the piston, thereby preventing the abrasion of the piston and cylinder and the breakage of parts.

WO 01/50020 A1